

**Product**

Hide&amp;Seek

Type: Digital print on Nonwoven Weight: 150-165g/m<sup>2</sup>**Environmental mark**

Fulfills the IGI:s trade standards

(IGI = International Wallpaper Manufacturers' Association)

**Product contents**

All wallcoverings from Eco-Boråstapeter are free from PVC, heavy metals and other environmental harmful substances. All inks and coatings are waterbased.

The wallcovering components	Total weight percent	Weight-percent	Specifications of the components composition	Contains substances from the:		
				Limit-list*	PRIO-list*	Allergy and ...*
Base	90-100%	40-60%	Cellulose (TCF)	---	---	---
		15-35%	Synthetic fibers and binder	---	---	---
		15-25%	Inorganic filler	---	---	---
		1-5%	Additives			
Ink	0-10%	0-10%	Organic pigments	---	---	---

\*Swedish State Chemical Inspection's Limitlist, PRIO-list and document "Allergy and chemical products"

Formaldehyde in combined form exists naturally in wood being used in production of paper. Analysis of wallcoverings therefore shows tracks of formaldehyde. The quantities though are essential lower than the valid limit.

**Usage**

The wallcovering can be used in all areas except wet areas such as bathrooms etc. Suitable adhesive is a machine adjusted adhesive.

**Emissions**

Determination of the emission factor for VOC\* and identification of dominating substances has been made at the Swedish Testing- and Research Institute according to the FLEC-method\*\*. The test results is below the quantitative detection limit (< 10µg/m<sup>2</sup> x h)

\* VOC=Volatile Organic Compounds

\*\* FLEC=Field and Laboratory Emission Cell

### **Colour fastness to light**

Very good colour fastness to light 6-8. The highest value is 8.

### **Packaging**

The wall covering rolls are delivered in PET tubes made from recycled PET.

In average 25 gr packaging is being used per kg wall covering.

The average transport volume (incl. packaging) per kg wall covering is about 4 dm<sup>3</sup>.

Return of packaging material to Mr Perswall is not possible.

### **Transport**

The wallcoverings are transported via trucks from our central warehouse in Borås, Sweden.

Eco-Boråstapeter is connected to the Swedish REPA-register. Organisations number: 556423-2824.

### **Care instructions**

#### **Care instructions**

Avoid water to get in contact with the surface:

- Use a dry cloth or a sponge.
- Can be vacuum-cleaned.
- Avoid water to get in contact with the surface..

### **Estimated lifetime**

Estimated lifetime of the wallcovering is 10-15 years..

### **Recycling and waste**

The wallcovering can be recycled as energy at combustion.

All excess inks are being reused in production.

No wallcovering waste is considered as hazardous waste.

In order to achieve and maintain necessary wallcovering strength and to fulfil Eco-Boråstapeter's quality standards no recycled material is included in the wallcovering.

### **Production**

Eco-Boråstapeter's emission of solvents is below existing limits for concession's permission according to the Swedish Environmental Protection Law.

### **Quality**

Eco-Boråstapeter is certificated according to the international quality standard ISO 9001, certificate number 10 59.

### **ECO-BORÅSTAPETER'S ENVIRONMENTAL POLICY**

Our target is that our production process and the products we produce  
should have the lowest possible impact on the environment.